

100% CUT 5 GLOVES 52#LS TPV HI-VI GLOVE



52LS TPV

Description

Dromex® 52#LS TPV HI-VI, high visibility gloves consist of a 100% Dromex® Cut 5 fibre with PU coating on the palm area and innovative TPV impact protection on the back and thumb provides protection against cut, abrasion and impact. Features excellent dexterity, enhanced power grip, lint free construction and UV resistance when exposed to light. For use in industries such as automotive, steel/glass, assembling, warehousing, mining, construction work, police and military.

Special Instructions

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The manufacturer has examined under the system for ensuring guality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment therefore it is the responsibility of the user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

All gloves should be thoroughly inspected before use to ensure no damage is present.

Compliance & Conformity

Complies with the requirements of CE type examinations EN420 for innocuousness, EN 388 for compliance with directive 89/686/EEC Mechanical Risks (4,5,4,2) and EN 407:2004 Thermal Risks for Heat and Flame (X1XXXX). Quality System conforms to ISO9001:2008 and environmental management system ISO 14001:2015 system certificates or acceptable equivalent.

Specifications

EN 388: XXXX

4542

X1XXXX

Style:	Pu palm dipped with TPV (Thermoplastic vulcanizate)
	knuckle and finger protection
Liner:	100% Dromex [®] Cut 5

- Palm: PU (Polyurethane) coated 1.5 mm \pm 5 %
- Back: 100% Dromex[®] Cut 5 fibre 1mm ± 5 % with TPV knuckle and fingers
- Cuff: Velcro closure for enhanced fit ± 140 g per glove (size 10) Mass:

Sizes Available

8-10

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool dry place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the glove.

Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below:

Wash up to	Do not use	Tumble dry	Do not	Do not
40C	chlorine	possible	iron	dry clean
40C	\boxtimes	•	\bowtie	\boxtimes

100% Dromex® Cut 5 gloves have proven that dry cleaning as well as laundering are suitable cleaning methods. We recommend that no bleaching or oxidising ingredients or any fabric softeners be used. Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

The drying process may cause felting on the fabric surface. Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove. Depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur. In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cvcle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Materials



- 1. Wing thumb
- 2. TPR padding in fingers
- 3. 5cm Neoprene cuff with a pull strap and loop velcro strap for fastening