

Dromex




ARC PROTECTIVE CUT LEVEL 5 GLOVES
CA420



CA420

EN 388:2016



3X33D

EN 407:2004



X1XXXX

Special Instructions

Please store the gloves far from sunshine and light. None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so it is therefore the responsibility of the user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

All gloves should be thoroughly inspected before use to ensure no damage is present.

Compliance & Conformity

Complies with the requirements of CE type examinations EN420 for innocuousness, EN 388:2016 Mechanical Risks (3,x,3,3,D) and EN 407 (X1XXXX) for compliance with directive 89/686/EEC. ASTM F2675/F2675M-13.

Specifications


Style:	Leather glove lined with aramid fibre
Liner:	100% aramid
Palm:	Cow split leather 1 mm ± 5%
Back:	Cow split leather 1 mm ± 5%
Cuff:	Shirred extended 16 cm cuff, 1mm ± 5%
Stitching:	Kevlar
Mass:	270±6 g per pair glove (size 11)

Sizes Available

8-11

Packaging, Storage & Obsolescence

Sold as a pair. Store in a cool dry / dark place. If stored correctly, the gloves physical properties will not change for up to three years. Packed in individual poly bags.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended, especially if potential hazards exist. Before removal from the hands, excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

How to decontaminate your leather glove.

Under no circumstances should leather submerged in water.

1. Prepare a lukewarm water solution using mild detergent.
2. Gently wipe your leather glove with a cloth.
3. In-order to reduce stiffening, allow the leather glove to dry naturally.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substance they were used for. Please consider recycling.

Materials



1. Wing thumb
2. Leather palm & fingers
3. Woven cotton binding
4. Aramid fibre lining

Marking



Description

Dromex® CA420 arc protective high cut level 5 and 51 CAL/CM² arc rated leather gloves provide hands with protection against burns, cuts and abrasion from the hazardous of a category 4 arc incidents. Provides high dexterity and comfort, making this glove the ideal solution in arc protection. Lined with aramid fabric and an extended 16cm shirred cuff, provides extra protection against burns and abrasion upon an incident.

The technical leather construction on the palm gives an excellent grip in oily conditions but also has a high durability and resistance to snatch, tear, cut and heat.

Suitable for use in industries where exposed to high voltage arc blast such as power companies, installation, maintenance, and repairs involving high voltage equipment.

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa
T. +27(31) 713 1960 E. info@dromex.co.za
www.dromex.co.za