


NITRILE 0056







NITRILE 0056

Description

Dromex[®] 0056, green flock lined Nitrile gloves protects the hands against many solvents and oil-based chemicals, whilst providing protection against abrasion, cuts, snags and punctures.

Impermeable to chemicals and microorganisms, features a raised pattern on palm, fingers and partially on the wrist for grip, with a curved finger design helps reduce hand fatigue.

Suitable for use when handling chemicals in labs, cleaning, janitorial applications and environmental clean-up. Used in industries such as chemical processing, oil refining petrochemicals, food processing, automotive assembly, painting, maintenance and machine operation.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, so it is therefore the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN420 for innocuousness EN388:2003, (3,1,0,1) for mechanical risks, EN374 - 2:2003 and EN 374 - 3:2003, protective gloves against dangerous chemicals and micro-organism for compliance with directive 89/686/EEC.

Specifications

Style:Wing thumb, flock lined, with anti-slip
patterned palm, finger and partial wristLiner:NitrilePalm:0.38 mm ± 5 %Back:0.38 mm ± 5 %Cuff:12cm open wrist cuff with pattern for
ease of glove removalMass:76g per pair (size 11)

CAT 🎹

EN 374-3 : 2003			
Name of Chemicals	Sulfuric Acid 96%	Sodium Hydroxide 40%	n-Heptane
Letter code of the product	L	К	J
Permeation Performance Levels	3	6	6

Sizes Available

7-11

Packaging, Storage & Obsolescence


Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool dry place away from sunlight. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition, if re-use is intended especially if potential hazards exist. Before removal from the hands, excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand & remove the gloves without the contaminant contacting the bare hands.

The gloves may then be de-contaminated as indicated below:



We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal lifecycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Materials



 Wing thumb
Raised palm & finger pattern
Open cuff

Marking

