

Dromex




NITROLITE



NITROLITE

EN 388: 2003



4131

Description

Dromex® Nitrolite, smooth finish palm coated nitrile gloves, provide hands with excellent grip performance in wet, oily and dry environments.

The nylon liner provides high dexterity, comfort and fit, whilst the nitrile coating protects the hand from high abrasion and cut resistance with strong tear resistant properties.

Suitable for applications where hand protection is required in manufacturing, and assembly, material handling and general maintenance industries.

Special Instructions

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for personal protective equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so, it is therefore the responsibility of the user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

All gloves should be thoroughly inspected before use to ensure no damage is present.

Compliance & Conformity

Complies with the requirements of CE type examinations EN420 for innocuousness, EN388 for Mechanical Risks (4,1,3,1). Quality System conforms to ISO9001:2008.

Specifications

Style:	Palm and finger coated nitrile gloves
Liner:	Grey nylon
Palm:	Nitrile coated 0,2 mm ± 5%
Back:	0,1 mm ± 5%
Cuff:	Nylon composite knitted wrist
Mass:	44 ± g per pair (size 10)

Sizes Available

7-10

Packaging, Storage & Obsolescence

Nitrolite gloves are packed in individual polybags and sold as 120 pairs per carton for shipping.

Store in a cool dry place and out of direct sunlight and UV light.


Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand & remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated as indicated below.

Dromex® Nitrolite gloves have proven that dry cleaning as well as laundering are suitable cleaning methods. We recommend that no bleaching or oxidising ingredients or any fabric softeners be used. Recommended washing temperature is up to 40°C with mild detergents. The drying process may cause felting on the fabric surface. Drying temperature should not exceed 70°C (158°F).



There is no remarkable impact on cut resistance during the normal life cycle of a glove. However depending on the glove construction, staining and cleaning method, the differences in shrinkage, weight loss, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Materials



1. Wing thumb
2. Nitrile coated fingers & palm
3. Knitted wrist

Marking



Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa
T. +27(31) 713 1960 E. info@dromex.co.za
www.dromex.co.za