


Dromex



GCRA Y COATED GLOVES

EN 388:2003



3143



GCRA Y

Description

Dromex® GCRA Y diamond groove rubber coated cotton gloves provides grip when handling slippery or abrasive objects and protects the hands against cut and puncture hazards.

Designed for handling applications in assembly, inspection, general maintenance, gardening, glass handling and fishing industries.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN420 for innocuousness and EN388 (3,1,4,3) for Mechanical risks in compliance with directive 89/686/EEC.

Quality System conforms to ISO 9001:2008

Specifications

Style: Rubber coated palm and fingers
Liner: Cotton
Palm: Rubber coated 1.1mm ± 5%
Back: 0.9mm ± 5%
Cuff: Composite knit wrist
Mass: ±100 g per pair (size 10)

Sizes Available

10

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping. Store in a cool dry place and out of direct sunlight and UV light. If stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right-hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

The gloves may then be decontaminated as indicated below:

- We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.
- Recommended washing temperature is up to 40°C with mild detergents.
- The drying process may cause felting on the fabric surface.
- Drying temperature should not exceed 70°C (158°F).

There is no remarkable impact on cut resistance during the normal life cycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, yarn strength and colour may occur.

In order to maximise the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Materials



1. Wing thumb
2. Rubber coated palm & fingers
3. Knit wrist

Marking

