

# Dromex



## D59 THERMAL JACKET



DW-D59FAOR-WJ

OR

NB

### Description

Dromex® D59 flame and acid treated thermal winter jacket is designed to protect the user from the hazards of accidental flame contact and acid splashes, reducing injury when working in hazardous environments.

This jacket is suitable for use in colder work environments, keeping the user warm whilst the 100% cotton satin weave finish and natural fibre construction makes this garment comfortable and breathable.

The Dromex DW-D59FA jacket is approved to the latest SANS 434 specification and has the SABS permit marking.

The D59 drill fabric construction is heavy duty and durable whilst the flame acid garment treatment technology resists the effects of flame contact and acid corrosion offering the user essential protection in the workplace.

This garment consists of the following:

- Collared jacket with internal hanger loop.
- High visibility flame retardant reflective tape on arms for enhanced visibility when working in poor lighting environments.
- A concealed heavy duty Vizlon zip and plastic press stud closure.
- 2 Large waist pockets, 2 bellow chest pockets with flap and metal press stud closures, left chest pocket with Dromex® sidewinder label.

- Sleeve cuffs have an adjustable strap with 2 position fastening allowance and capped press studs.
- Double needle topstitching on shoulder and armhole seams for added durability.
- Flame retardant and acid resistant embroidery on arm for garment identification.

This garment is suitable for use in general work environments such as engineering, smelting operations, mining, construction, oil and gas, petroleum, maintenance, repairs and welding industries.

### Special Instructions

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer.

The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection.

This flame and acid garment is designed to accommodate the basic safety requirements and standards for Personal Protective Equipment.

The information contained herein is intended to assist the wearer in the selection of personal protective equipment.

Actual conditions of use cannot be directly simulated in a test environment therefore it is the responsibility of the end user and not the manufacturer or supplier to determine the garment suitability for the intended use.

Flame and acid protective garments should be thoroughly inspected before use to ensure no damage is present.

Should there be visible damage such tears or burn holes it is recommended to replace the garment immediately.

### Specifications

Style:	4 Pocket long sleeve thermal jacket with high visibility reflective tape on arms. Double lined winter jacket. Orange (DW-D59FAOR-WJ).
Fabric composition:	100% Cotton (outer and lining).
Mass:	320gsm Flame retardant fabric (outer), 100gsm Flame retardant wadding interlining, 220gsm Flame retardant lining.
Reflective:	50mm Silver flame retardant tape.
Additional:	Also available in Navy Blue (DW-D59FA-WJ).



DW-D59FA-WJ

### Compliance & Conformity

- Garments comply to the latest SANS 434 standard (This standard specifies requirements for cut, make and trim of jackets).

#### This standard makes reference to the following relevant standards:

SANS 1362	Sewing threads.
SANS 1822	Slide fasteners.
SANS 5278	Sewing stitches per unit length.
SANS 10235	Fibre-content labelling of textiles and textile products.
SANS 50471	High-visibility warning clothing for professional use.

The fabric is to SANS 1387-4 for D59 drill fabric, 4/1 satin weave @270gsm, 37 thread per cm weft and 19 threads per cm warp. The breaking strength is 940 N warp and 510 N weft.

- **Flame retardant fabric is tested to SANS 1423-1 for textile fabrics of low flammability for apparel:**

Class B Category 1:

The fabric ignites within a given time period and might continue to flame but at a rate of flame propagation that is within a specified limit. Surface Flash None.

Ignition time (seconds) \_ 20 sec.

Rate of flame propagation 5mm/s.

\*\* Note this is a test situation for the fabric and does not cancel or imply otherwise to the labels wash instruction.

- **Flame retardant silver retro-reflective tape is tested to SANS 50471:2006 (EN 471:2003 + A1:2008) and SANS 1423-1:2008 for textile fabrics of low flammability for apparel:**

High visibility warning protective clothing capable of signalling the users presence visually, intended to provide conspicuity of the user in hazardous situations under any light conditions by day and under illumination by vehicle headlights in the dark. Performance requirements are included for retro-reflection and not for the entire garment.

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa  
T. +27(31) 713 1960 E. info@dromex.co.za

www.dromex.co.za

Disclaimer

Dromex reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex does not assume any liability arising out of the application or use of any product described herein. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Latest update: 22/08/2022

**Acid resistant fabric is tested to ISO 6530:2005 for protection against liquid chemicals:**

- Two levels of the potential performance are assessed by this method of testing to meet with possible requirements for protection against:
- Deposition on the surface of a material at minimal pressure, of spray droplets up to coalescence or occasional small drips.
  - Contamination by a single low-volume splash or low-pressure jet, allowing sufficient time to divest the clothing or take other action as necessary to eliminate any hazard to the wearer from chemical retained by the protective garment or in circumstances where pressure is applied to liquid contaminants on the surface of the clothing material, as a result of natural of the wearer (flexing of contaminated areas of clothing at arms, knees, shoulders) and contact with contaminated surfaces (e.g. walking through sprayed foliage).

Acid resistance for protective clothing against liquid chemicals for performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals. The acid resistant finish is primarily a liquid proof coating that is not destroyed by the action of acids or other chemicals. It doesn't allow the cloth to be wetted by the acids and is therefore "acid resistant".

- The test chemicals are:
- Hydrochloric Acid (HCl) 32%
  - Sulphuric Acid (H2SO4) 24%
  - Nitric Acid (NHO3) 65%
  - Sodium Hydroxide (NaOH) 40%

There is no SANS specification for Acid Resistance therefore alternate testing is done in the absence of a national standard. The tests are done to the ISO 6530:2005 and the chemical selection and concentration to the withdrawn DIN32763 standard.

**Packaging, Storage & Obsolescence**

Dromex® DW-D59FA-WJ are packed in individual polybags and sold as 5 jackets.

**Cleaning & Maintenance**

- The following suggestions will help keep your garment safe and neat:
- D59 Garments can be cleaned by home cleaning or commercial laundering provided all the recommended conditions and settings are adhered to.
- Should home procedures not remove contaminants, then dry cleaning is recommended.
- Our recommended cleaning for these garments is as follows:
  - Flame Retardant garments should not be washed with personal non-flame-retardant clothing to avoid contamination by flammable materials.
  - Pre-treat greasy stains and wash the garment in warm water with a light cleaning solvent.
  - Do not use Hypochlorite bleach or detergents containing Hypochlorite bleach as fading may occur.
  - Do not tumble dry.



**Sizes Available**

Navy Blue (DW-D59FA-WJ), XS - 7XL.  
Orange (DW-D59FAOR-WJ), XS - 3XL.

Size designation	Measurements of finished garment (cm)			
	Sleeve length	Length	Chest	Shoulder
<b>XS</b>	63.5	78	62	20.5
<b>S</b>	64.5	80	65	21
<b>M</b>	65.5	81.5	70	21.5
<b>L</b>	67	83.5	74	22
<b>XL</b>	68	85.5	78	22.5
<b>2XL</b>	69	87.5	82	23
<b>3XL</b>	70	89.5	86	23.5
<b>4XL</b>	71	91.5	90	24
<b>5XL</b>	72	93.5	94	24.5
<b>6XL</b>	73	95.5	98	25
<b>7XL</b>	74	97.5	102	25.5


**Marking/Labels**

DROMEX




Position:  
Jacket-Neck (inside)

SIZE



Position:  
Jacket-Neck

PRODUCT & YOM LABEL



Position:  
Jacket-Neck

PRODUCT STANDARD



SANS 1387-4,  
SANS 1423-1,  
SANS 434  
ISO6530: 2005

**Disposal**


All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Please consider recycling.

EMBROIDERY FR ACID RESISTANT



Position:  
Jacket-Right arm

INFORMATION LABEL



Position:  
Jacket-Neck

SIDEWINDER



Position:  
Jacket-Top pocket