



PRODUCT CODE: HS-INDHEL-WH

PRODUCT DESCRIPTION: Industrial helmet with adjustable chin strap

PRODUCT COMPLIANCE

CERTIFICATION	EN397:2012 + A1:2012
WEIGHT	350gms
COLOUR AVAILABILITY	White
PACKAGING	Individually packed in a box, 12 units per carton
SIZING	Adjustable to fit heads with circumference of 52cm to 63cm

MATERIALS + DESIGN

- Outer shell made with acrylonitrile butadiene styrene (ABS) & polycarbonate (PC).
- High protective shell exterior.
- Wide aeration holes with covers to prevent debris entry.
- Inside protection in high-density polystyrene which aids with impact resistance protection.
- Inner textile and headband, removable and washable.
- Polyester webbing chin strap which includes a polypropylene chin cup.

TECHNICAL FEATURES

- Protection from falling objects.
- Helmet supplied with an adjustable 3-point chin strap.
- Wheel ratchet provides quick & easy size adjustment.
- Contoured webbing for comfortable fit.
- Has a reduced peak for better field of vision.

USER ADVICE

- This helmet is made to absorb the energy from falling objects and even though such damaged may not be readily apparent any product subjected to severe impact should be replaced.
- If there are any cracks, chips or deformations ensure that the helmet is inspected by a competent person and is still safe to use.
- Do not modify or remove any of the original component parts of the product.
- This product should not be adapted for the purpose of fitting attachments.
- Do not apply paints, solvents, adhesives or self-adhesive labels.
- This product may be adversely affected by certain chemicals.
- Clean any part of the safety helmet with warm soapy water and dry with a soft cloth.

ADJUSTMENT AND FITTING

- To ensure adequate protection is provided by the product, the wheel ratchet at the back of the helmet must be adjusted according to the size of the user's head. This must be done until the helmet feels comfortable and snug on the user's head. Do not over tighten.

STORAGE

- When not in use, it is recommended to store the industrial helmet in a clean and dry polybag or case for optimal protection
- Storage temperature range: -10°C to +50°C.

DURATION OF USE

- The functional life of the product is determined by work conditions and maintenance.
- To be inspected for damage regularly by a competent person.
- If the shell shows any signs of damage or discolouration from UV damage, it must be replaced immediately.
- As long as the product passes the inspection criteria, it may remain in service up to a maximum of 5 years.

WARNINGS

- Helmet chin strap must be connected when climbing or when used to ensure that the helmet remains in place in the event of a fall.
- Working at Heights training must be completed prior to using this product if used when working at heights.

SUGGESTED ENVIRONMENTS

- Work at Heights.
- Confined Space.
- General Work.