

16INCH SUPERIOR LINED LEATHER GLOVES





Description

Dromex® WELD/16GR protective gloves are designed for use in welding related operations.

These gloves consist of premium green dyed cow split leather, are cotton fleece lined and fully welted with a 16-inch shoulder length cuff.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Compliance & Conformity

Complies with the requirements of CE type examinations EN 420 for innocuousness, pH value >3,5 <9,5, Chromium VI in leather shall not exceed 3,0 mg/kg and the size is correct. Compliance with directive 89/686/EEC, EN 388:2016 Mechanical Risks.

Quality System conforms to ISO 9001:2008 and environmental management system, ISO 14001:2015 system certificated or acceptable equivalent.

Specifications

EN 388: 2016

Style: Green 60cm length gunn cut, wing thumb, welted

> sewn with cotton welding glove 0.8mm ± 5% cotton fleece

Liner: Palm: Green dyed cow split leather 1mm ± 5% Back: Green dyed cow split leather 1mm ± 5%

Cuff: 16-inch (40cm) cow split leather shoulder cuff lined

with denim cotton and yellow trim

Mass: ± 600g Per pair

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 60 pairs per carton for shipping. Store in a cool, dry place. Stored correctly, the gloves physical properties will not change for up to two years.











Cleaning & Maintenance

Gloves should not be left in a contaminated condition if re-use is intended, especially if potential hazards exist. Before removal from the hands, excess contaminant should first be removed from the gloves. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands.

How to decontaminate your leather glove.

Under no circumstances should leather submerged in water.

- 1 Prepare a lukewarm water solution using mild detergent.
- 2 Gently wipe your leather glove with a cloth.
- 3. In order to reduce stiffering, allow the leather glove to dry naturally.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Size Available

Code	Size	Palm Length
WELD/16GR	L/10	125mm (±5mm)

- * As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.
- * Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accomodate a wearer's preferences.

Measurement Guide



Marking



Materials



- 1. Winged thumb
- 2. Gunn cut
- 3. Fully welted

Dromex: Unit 1, 1 Blase Road, New Germany, 3620, South Africa T. +27(31) 713 1960 E. info@dromex.co.za www.dromex.co.za